

KEY SPECIFICATIONS**— Triple Scabblers Side Handle Bush Hammer Head**

| | |
|---|---------------------------------|
| Part Number | 153.5250 |
| Weight (kg) | 5.2 |
| Length (mm) | 450 |
| Working Height (mm) | 160 |
| Blows Per Min (BPM) | 2400 x 3 |
| Air Consumption (lps - cfm) | 7 - 15 |
| Air Pressure | 6.2 bar (90 psi) |
| Air Inlet | 3/8" NPT (c/w 3/8" BSP Adapter) |
| Noise Level (db (A)) | 98 |
| Noise Level (bd (A)) | 111.3 |
| Vibration level (Aeq m/s ²) Primary | 8.7 |
| Vibration level (Aeq m/s ²) Secondary | 13.5 |
| Piston Diameter (mm) | 27 |
| Piston Length (mm) | 111.75 |
| Piston Stroke (mm) | 26.5 |

— Triple Scabblers Side Handle Cruciform Head

| | |
|---|---------------------------------|
| Part Number | 153.5200 |
| Weight (kg) | 5.2 |
| Length (mm) | 450 |
| Working Height (mm) | 160.00 |
| Blows Per Min (BPM) | 2400 x 3 |
| Air Consumption (lps - cfm) | 7 - 15 |
| Air Pressure | 6.2 bar (90 psi) |
| Air Inlet | 3/8" NPT (c/w 3/8" BSP Adapter) |
| Noise Level (db (A)) | 98 |
| Noise Level (bd (A)) | 111.3 |
| Vibration level (Aeq m/s ²) Primary | 8.7 |
| Vibration level (Aeq m/s ²) Secondary | 13.5 |
| Piston Diameter (mm) | 27 |
| Piston Length (mm) | 111.75 |
| Piston Stroke (mm) | 26.5 |

— Triple Scabblers with Shroud Cruciform Head Short Handle

| | |
|---|---------------------------------|
| Part Number | 139.5390 |
| Weight (kg) | 5.2 |
| Length (mm) | 450 |
| Working Height (mm) | 160.00 |
| Blows Per Min (BPM) | 2400 x 3 |
| Air Consumption (lps - cfm) | 7 - 15 |
| Air Pressure | 6.2 bar (90 psi) |
| Air Inlet | 3/8" NPT (c/w 3/8" BSP Adapter) |
| Noise Level (db (A)) | 98 |
| Noise Level (bD (A)) | 111.3 |
| Vibration level (Aeq m/s ²) Primary | 8.7 |
| Vibration level (Aeq m/s ²) Secondary | 13.5 |
| Piston Diameter (mm) | 27 |
| Piston Length (mm) | 111.75 |
| Piston Stroke (mm) | 26.5 |

— Triple Scabblers with Shroud Cruciform Head

| | |
|---|---------------------------------|
| Part Number | 139.5392 |
| Weight (kg) | 5.2 |
| Length (mm) | 450 |
| Working Height (mm) | 160 |
| Blows Per Min (BPM) | 2400 x 3 |
| Air Consumption (lps - cfm) | 7 - 15 |
| Air Pressure | 6.2 bar (90 psi) |
| Air Inlet | 3/8" NPT (c/w 3/8" BSP Adapter) |
| Noise Level (db (A)) | 98 |
| Noise Level (bD (A)) | 111.3 |
| Vibration level (Aeq m/s ²) Primary | 8.7 |
| Vibration level (Aeq m/s ²) Secondary | 13.5 |
| Piston Diameter (mm) | 27 |
| Piston Length (mm) | 111.75 |
| Piston Stroke (mm) | 26.5 |