

**LOW VIBRATION POLE SCABBLER**

**VL LRS55**



**THE VL LRS55 IS A POWERFUL LONG REACH SCABBLER FOR VERTICALLY PREPARING HARD TO REACH AREAS.**

At 1.4 metres in length it allows scabbling below the reinforcement bar.

The powerful blow quickly removes concrete without damaging the underlying substrate.

Vibro-Lo™ low vibration system fitted as standard, helping to reduce risks to operators of vibration related injuries.



Low vibration

**FEATURES & BENEFITS**

- Replaceable pin fit carbide tipped scabbling heads
- Long handle for extended reach into inaccessible areas
- Angled air inlet to direct hose away from operator
- Hand guard to protect operator

**APPLICATIONS**

- Heavy scabbling of hard to access areas such as below re-inforcement bars and between shuttering
- Scabbling of corners, edges and joints
- Fast removal of material
- Aggressive keying without damaging the substrate



SCABBLING CONCRETE



CONCRETE REDUCTION











TEXTURING CONCRETE



**LOW VIBRATION POLE SCABBLER**

**VL LRS55**

**KEY CONSUMABLES & ACCESSORIES**

Image	Part Number	Description
	441.5359	<b>Scabblers Head 5 Point Bush</b> Pin fit - including pin Rough pitted profile, ideal for application of fresh concrete or coatings
	441.5369	<b>Scabblers Head 9 Point Bush</b> Pin fit - including pin Rough pitted profile, ideal for application of fresh concrete or coatings
	441.5360	<b>Scabblers Head Cruciform</b> Pin fit - including pin Flatter surface profile, ideal for fast reduction of material
	446.5000	<b>VL LRS55 Service Kit</b>
	815.5550	<b>Whip check</b>
	859.1580	<b>3/8" BSP inline lubricator</b>
	458.1580	<b>Whip Hose &amp; Oiler Assembly</b> Consists of whip hose, whip check and 3/8" lubricator
	843.0752	<b>3/8" Air Hose</b> Complete with couplings 15m length

**TECHNICAL DATA**

Model	Part Number	Weight (kg)	Length (mm)	Blows per minute (BPM)	Air Consumption (lps - cfm)	Vibration Level (Aeq m/s <sup>2</sup> )
VL LRS55 c/w 5 Point Scabblers Head	150.5320	21.5	1270	1300	11.6 - 24.6	4.2 
VL LRS55 c/w 9 Point Scabblers Head	150.5321	21.5	1270	1300	11.6 - 24.6	4.2 

Note: Can be converted to a pole compactor by changing the scabblers head with a compactor foot.